

Technical Data Sheet

Syntarex™ E-SBR 1502

EMULSION – STYRENE BUTADIENE RUBBER



Description

Syntarex™ E-SBR 1502 is a reprocessed emulsion polymerized based SBR. It is reprocessed by Cinar Kaucuk in Denizli, Turkiye. Syntarex™ E-SBR 1502 provides good processability, mechanical properties and abrasion resistance.

Properties	Unit	Value	Test Method
Mooney Viscosity*	MU	50 – 60	ASTM D 1646
Bound Styrene	% wt.	20 - 25	SM**
Moisture Content	% wt.	1.5 max.	Internal Method
Density	(g/cm3)	0.96	Internal Method
Antioxidant		Non-Staining	SM**

*ML 1+4 (100°C) unmassed sample ** Supplier Method

Color*

Amber, Amber to dark.

*Amber color are suitable for colored compounds.

Packaging

Syntarex™ E-SBR 1502 is in bale form which is wrapped in a low melt dispersible bag. Each bale is about 22 kg ± 1 kg. Each wooden box has 40-45 bales which means each box is about 900-1000 kg.

Applications



Solid Tyre



Rubber Retread



Shoe Sole



Rubber Conveyor Belt



Rubber Compound

The properties data and information here are estimated values based on our experience and customer feedback. This TDS creates no guarantee, warranty, or liability of the products' properties. Herewith Cinar Kaucuk declares that this is non-prime synthetic rubber, and it is the buyer's responsibility to test and inspect our products to define useability for the buyer's application.

Syntarex™ is a trademark of Cinar Kaucuk.